



PROTECTOR for CONCRETE PAVERS (iN)

NATURAL LOOK - MATTE FINISH - WATER BASED

(121-313/1 gal.)

(121-316/5 gal.)

UPDATE

November 26, 2015

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
U.S.A. and Canada: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Recommended for pool decks, patios, Walkways and retaining walls

PROPERTIES

- Preserves the natural look of pavers
- Ideal for slip-prone surfaces
- Stain guard - repels contaminants
- Water based

DESCRIPTION

Made of water- and oil-repellent agents, Natural Look iN Protector is specially designed to protect concrete pavers. It prevents deterioration due to chemical products such as de-icing salts, while providing resistance to acids and alkalis. Its active agents form an invisible bond that stops the penetration of contaminants, facilitating the maintenance of pavers. Water based, iN Protector does not release unpleasant fumes, and it is environmentally friendly.

DIRECTION

BEFORE YOU BEGIN

• Do not apply to stamped concrete. • Application to natural stone or wet-cast pavers: Contact Techniseal® for more information: 1 800 465-7325. • Apply only to bare material* or to material previously sealed with this product. • Wait until surface is no longer water-repellent before recoating (minimum 2 years). • With the appropriate Techniseal® stripper, remove any unknown coating that was previously applied. • **ALWAYS TEST** on a small hidden area of approximately 4 sq. ft. to ensure that result meets your expectations (see Warranty).

*ABSORPTION TEST: Sprinkle a few drops of water on surface. If water is absorbed, move on to the next point. If water is repelled, do not apply this product.

SURFACE PREPARATION (ESSENTIAL)

1. Cover vegetation, vehicles and adjacent surfaces that are not to be treated.
2. Remove stains with the appropriate Techniseal® stain removers.
3. Prepare the entire surface with Techniseal® Paver Prep (efflorescence cleaner) as directed on product label.

APPLICATION

Application Conditions:

- Surface must be clean, dry and warm to the touch.
- Temperature must be between 50°F and 86°F.
- No rain forecasted for the next 24 hours.
- Sprinkler system must be turned off.
- Use a consistent application method over entire surface.

Necessary Tools:

- 3/8" polyester nap roller, and paint tray
- Low-pressure airless sprayer (< 50 psi) or pump sprayer (optional)

Do not dilute. Shake well or stir product before and during application. Work in sections of no more than 100 sq. ft. Apply in such a way that you can return to each section without walking on fresh protector (2 coats wet-on-wet technique).

Sprayer Application (Best Practice): Saturate the surface with a first coat of protector. Remove excess with the roller. Immediately upon completion of a section, apply a second coat following the same method as before. Repeat for subsequent sections, maintaining a wet edge in order to prevent overlap marks.

Roller Application: Saturate the surface with a first coat of protector, avoiding accumulation of excess product. Immediately upon completion of a section, apply a second coat following the same method as before. Maintain a wet edge in order to prevent overlap marks.

Traffic: Pedestrian: 24 h. / Vehicular: 48 to 72 h. Block access during that period.

CAUTION

- Any new concrete product has the potential to produce efflorescence (whitish salts) on its surface. This Protector will not trap efflorescence, which will disappear by itself after prolonged exposure to weathering.
- Do not attempt sprayer application on windy days.
- Do not apply this product over a blotchy or hazed surface.
- An over-accumulation of product could make dust stick onto the surface.

COVERAGE

1 gal. covers up to 120 sq. ft. for a two-coat application. The application of two coats is mandatory.

STORAGE

Store in a cool, dry place.

CLEANING & DISPOSAL

Wash tools and hands with warm soapy water. Consult your retailer or community agency for disposal of empty containers or unused product.

PACKAGING

Product Code	Retail Size	Pro Size	Units per box	Units per pallet
121-313	1 gal.	-	2	180
121-316	5 gal.	-	-	48
121-318	-	55 gal.	-	4

WARNING

PROTECTOR for CONCRETE PAVERS - iN

Read label before use. KEEP OUT OF THE REACH OF CHILDREN. If medical advice is needed, have product container or label at hand.

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 5.4%

Coating Category: Waterproofing Concrete/ Masonry Sealers (VOC Concentration Limit: 100g/L)

EMERGENCY PHONE: CANUTEC (613) 996-6666. SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.

Techniseal®, 300 Liberté, Candiac (Québec), Canada J5R 6X1

SHIPPING

Land and sea

NOT REGULATED

LIMITED WARRANTY

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq. ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.