

Rust remover



(141-521 / 1 L)

UPDATE

December 10, 2015

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
Canada and U.S.A.: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Concrete pavers, slabs and walls

PROPERTIES

- Effectively removes stains caused by steel, rusted metal objects, fertilizers, etc.
- Contains no muriatic acid

DESCRIPTION

Techniseal[®] Rust Remover for pavers takes out rust from pavers made of concrete. It effectively dissolves stains caused by dripping rusted water, steel streaks, fertilizer granules¹, etc. Since it contains no muriatic acid, it won't damage the material. For bare or previously sealed surfaces.

¹To remove fertilizer stains from a large surface, it is recommended to use Techniseal[®] Pre-Seal Cleaner (141-534).

DIRECTIONS

BEFORE YOU BEGIN

- Wear rubber gloves and safety goggles. • ALWAYS TEST on a small hidden area to ensure that result meets your expectations.

APPLICATION

Wet the stain and cover it with Rust Remover; using a small nylon scrub brush such as the Techniseal Stain remover brush (145-910), scrub the stain until dissolved; rinse immediately with water. If rust persists, repeat the operation.

IMPORTANT : Pavers may appear spotted after the use of Rust Remover. This is called a "clean stain". For uniform results, clean the entire surface with Techniseal[®] Pre-Seal Cleaner (141-534). Rust streaks left by metal snowploughs may be difficult to remove. **Do not use on natural stone wet-cast pavers or poured concrete.**

PACKAGING

Product code	Size	Units per box	Units per pallet
141-521	1 L	6	480

WARNING

CAUSES BURNS DANGEROUS. FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. Do not mix with Alkali. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Use only in a well-ventilated area. Handle with care. **KEEP OUT OF REACH OF CHILDREN.** Wear protective gloves and eye/face protection: Chemical splash goggles or face shield. Use chemical-resistant, impervious gloves. Wear appropriate respirator when ventilation is inadequate. **FIRST AID TREATMENT Contains:** Phosphoric acid. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

SHIPPING

Land

Transported in limited quantity

Sea

UN1805

Phosphoric acid, solution

Class: 8

PG: III

LIMITED WARRANTY

Techniseal® warrants this Remover against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim.