



## PAVER RESTORER

(121-604 / 1 gal.)

### UPDATE

---

#### November 26, 2015

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: [techniseal.com](http://techniseal.com)  
U.S.A. and Canada: dial 1 800 465-7325  
Others: dial (514) 523-8324 (Canada)

### APPLICATIONS

---

- Pavers and slabs made of concrete or natural stone
- Driveways, patios, terraces, commercial parking lots, pedestrian areas, etc.

### PROPERTIES

---

- Removes cement and mortar jointing haze
- Removes stains generated by pavers and slabs cuts

### DESCRIPTION

---

Techniseal® Paver Restorer removes the haze left after grout and masonry work on tiles and pavers made of concrete or clay. It works efficiently without discoloring or damaging the surface. Unlike muriatic acid, Techniseal® Paver Restorer releases very little odor and is environmentally friendly.

### DIRECTIONS

---

#### BEFORE YOU BEGIN

- Do not use on natural stone, wet-cast pavers and stamped or poured concrete.
- Wear rubber gloves and safety goggles.
- **ALWAYS TEST** on a small hidden area of approximately 4 sq. ft. to ensure that result meets your expectations
- **Never** use this product without first consulting with local authorities regarding the application of such products, waste management and run-offs.
- Do not apply under blazing sun.
- Protect people, vehicles, property, vegetation, and other surfaces not set for cleaning from product, residue, splash, fumes and wind drift.

#### PREPARATION

**SURFACE WETTING:** To reduce the penetration of Paver Restorer into sand joints and thus make product easier to rinse, first wet the surface to saturate joints with water; then let the surface dry, and apply product.

**DILUTION:** Dilution must be adjusted according to the amount of haze present on the pavers. In a plastic container, dilute the product in water. Always pour the product in water, not the other way around. The recommended dilution ratio is 1 part product in 1 to 4 parts water, depending on the severity of the haze. **ALWAYS TEST** the dilution on a small area first, in order to clean the surface without damaging or discoloring the material. If haze persists, reapply product using the proper dilution.

**Newly installed polymeric sand:** Wait at least 30 days before applying the product.

## APPLICATION

### Application Conditions:

- Surface must be dry, warm to the touch and free of debris.
- Temperature must be between 50°F and 85°F.
- Use a consistent application method over entire surface.

**Important:** Do not apply product with a mop or a broom. Do not apply under a blazing sun. **Never** let the cleaning solution dry on the surface; keep it wet at all times until it is completely rinsed off. **Never** apply the product at full strength.

Clean one section of 200 sq. ft. at a time. On each section, starting from the bottom of the slope, cover surface with diluted solution, making sure to cover the whole section without leaving any dry spots. Next, gently scrub the surface using a street broom; rinse immediately and thoroughly, until all traces of foam disappear, before proceeding to another section. In cleaning each section, overlap the edges of adjoining sections to ensure that no uncleaned strips are left between them. Once all the sections have been cleaned, rinse thoroughly and let dry. If there is any haze left on the surface, repeat cleaning.

## COVERAGE

1 gal. of product allows the cleaning of approximately 200 sq. ft. The coverage will depend on the severity of the haze.

## STORAGE

Store in a cool and dry place, away from the sunlight and with adequate ventilation.

## PACKAGING

Product code	Size	Units per box	Units per pallet
121-604	1 gal.	4	144
121-606	5 gal.	—	48

## WARNING

---



### PAVER RESTORER

#### WARNING

May be corrosive to metals.

Harmful if swallowed.

Causes serious eye irritation.

Causes skin irritation.

May cause respiratory irritation.

Read label before use. KEEP OUT OF THE REACH OF CHILDREN. If medical advice is needed, have product container or label at hand.

Wear protective gloves: > 8 hours (breakthrough time): Nitrile gloves. Wear eye or face protection. Keep only in original container. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Absorb spillage to prevent material damage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Store locked up. Store in corrosive resistant container with a resistant inner liner.

Dispose of contents and container in accordance with all local, regional, national and international regulations

Max VOC: less than 4%

**EMERGENCY PHONE: CANUTEC (613) 996-6666. SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT**

Techniseal®, 300 Liberté, Candiac (Québec), Canada J5R 6X1

## SHIPPING

---

### LAND AND SEA

NOT REGULATED

## LIMITED WARRANTY

---

Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq. ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.